

EXHAUST SYSTEM COMPONENTS



WIRE REINFORCED EXHAUST HOSE

| PART NO. | I.D SIZE |
|----------|---------------|
| | INCHES / mm |
| 7905-01 | 1 1/4 / 45mm |
| 7905-02 | 2 / 51 mm |
| 7905-03 | 2 1/2 / 63 mm |
| 7905-04 | 3 / 76 mm |
| 7905-05 | 3 1/2 / 90 mm |
| 7905-06 | 4 / 100 mm |
| 7905-07 | 5 / 127 mm |
| 7905-08 | 6 / 152 mm |

TEXTILE REINFORCING WIRE HELIX
TEMP -35°C TO +90°C
TWIN BROWN STRIPE



WATER LOCK/SILENCER

| PART NO. | I.D SIZE |
|----------|----------------------------|
| 7901-01 | 45 mm / 45 mm (3 Litre) |
| 7901-02 | 50 mm / 50 mm (7 Litre) |
| 7901-02E | 50 mm / 50 mm (5 Litre) |
| 7901-03 | 63 mm / 63 mm (7.5 Litre) |
| 7901-04 | 76 mm / 76 mm (7.5 Litre) |
| 7901-05 | 90 mm / 90 mm (15 Litre) |
| 7901-06 | 100 mm / 100 mm (15 Litre) |



NOTE: TYPE "E" 45° OUTLET
STAINLESS STEEL ANTI SIPHON UNIT
WITH NO VALVES OR MOVING PARTS

SKIN FITTING TRANSOM 45 C

| | |
|---------|--------|
| 7904-01 | 45 mm |
| 7904-02 | 51 mm |
| 7904-03 | 63 mm |
| 7904-04 | 76 mm |
| 7904-05 | 90 mm |
| 7904-06 | 100 mm |

EXHAUST GAS/WATER SEPERATORS

| | |
|---------|-------|
| 7903-03 | 51 mm |
|---------|-------|

SYPHON BREAK

| | |
|---------|----------|
| 7902-01 | 13mm (A) |
| 7902-02 | 16mm (A) |
| 7902-03 | 25mm (B) |
| 7902-04 | 19mm (B) |



STD TYPE



SYPHON BREAK



45 C transom, with thumpet shaped outlet.

The Water Separator is designed for generator installations where the silence of the exhaust system is essential. The water separator eliminates the gurgling sounds in the water damped exhaust outlet by separating the water from the gas. The constructions of the separator is with two stainless steel ends mounted in a rubber bellow. It is also suitable for main engines.



The Powerful Gem