









**YANMAR STANDARD ACCESSORIES**  
**COOLING SYSTEM & SIPHON BREAKERS**

PART NAME	IMAGE	DESCRIPTION
913-VL-05		1/2" (12.7mm)Vented Loop - Marine Type 316 S/S with Poppet Valve
913-VL-06		5/8" (15.8mm)Vented Loop - Marine Type 316 S/S with Poppet Valve
913-VL-07		3/4"(19mm)Vented Loop - Marine Type 316 S/S with Poppet Valve
913-VL-10		1"(25.4mm)Vented Loop - Marine Type 316 S/S with Poppet Valve
<p><b>Marine - Vented Loop type with a S/S spring to hold the poppet valve closed. A vacuum will pull the poppet open permitting air to go into the system. The vacuum breaker is normally closed. It does not require the pressure of the system to close the breaker poppet valve. When water passes through the cented loop it does not contaminate the poppet seat because the poppet is closed. Liquid will not escape when the poppet is closed.</b></p>		
SYPHON BREAK S/STEEL		1 1/4 "(32mm) Vented Loop - Marine Type 316 S/S
SYPHON BREAK S/STEEL 6LP		1 1/2" (38mm) Vented Loop - Marine Type 316 S/S

**YANMAR STANDARD ACCESSORIES**  
**COOLING SYSTEM & SIPHON BREAKERS**

PART NAME	IMAGE	DESCRIPTION
<b>Water Strainer 12mm Plastic Type</b>		50 LTS/MIN 12mm (0.5") to suit Strainer only - No fittings
<b>Water Strainer 16mm Plastic Type</b>		80 LTS/MIN 16mm (5/8") to suit Strainer only - No fittings SUITS - GM/YM SERIES MASE IS2.5 - IS10.8
<b>Water Strainer 20mm Plastic Type</b>		120LTS/MIN 20mm (3/4") to suit Strainer only - No fittings SUITS - MASE IS12 - IS16
<b>Water Strainer 25mm Plastic Type</b>		210 LTS/MIN 25mm (1") to suit Strainer only - No fittings SUITS - JH3/4 SERIES MASE IS18 - IS27
<b>Water Strainer 32mm Plastic Type</b>		330LTS/MIN 32mm (1¼") to suit Strainer only - No fittings SUITS 4LHA-HTP
<b>Water Strainer 40mm Plastic Type</b>		470 LTS/MIN 40mm (1.5") to suit Strainer only - No fittings SUITS - 4LHA-DTP/STP 6LYA ONLY BY SERIES